KIERA ONE PIECE TOILET 4.8LPF / 1.28GPF OR 3LPF / 0.8GPF

☐ 4710BNW Lined Tank □ 4710BNWU **Unlined Tank**

PRODUCT SPECS

- High efficiency dual flush toilet
- 4.8Lpf / 1.28Gpf or 3Lpf / 0.8Gpf
- Elongated bowl with concealed skirted trapway
- Vitreous china
- 17" Plus Height for greater comfort
- White and chrome top push button
- 12" (305mm) Rough-in
- 2" Fully glazed ball pass trapway
- 3" Dual flush valve
- Siphon jet flush action
- Water surface: 71/8" x 51/2" (240mm x 170mm)
- Decorative white sides caps included
- Smooth close toilet seat included

DIMENSIONS

391mm W x 725mm D x 765mm H 15" W x 28½" D x 30%" H

COMPLIANCE CERTIFICATIONS

Meets or exceeds the following:

- IAPMO cUPC
- ASME A112.19.2 / CSA B45.1
- LEED Compliant
- US EPA WaterSense
- MaP Premium Tested 1000g

SHIPPING

Cube 9.39 GW 92.5 lbs





NOTES: This toilet is designed to rough-in at a minimum dimension of 305mm (12") from finished wall to C/L of outlet. Supply

line not included with fixture and must be ordered separately.

Important: Dimensions of fixtures are nominal and may vary within the range of tolerances establishedby ASME standard A112.19.2. These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

